

## PU Anticolor

### 1. PRODUCT DESCRIPTION

Special waterbased 2 part polyurethane lacquer. With especially high cross-linking density, thereby providing higher resistance to colourants, plasticizers and chemicals. Permanent surface finish for the long-term protection of floors. For use after installation or renovation of floor coverings. For building areas subject to frequent chemicals on the floor, e.g. hairdresser's salons and medical areas. If maximum wear resistance is required instead of extra chemical resistance, we recommend the use of PU Sealer. For professional use only.

- Recommended in healthcare for cleanability and optimal disinfection. Fulfills requirements of TRBA 250 and DIN 13063.
- Reduces dirt adhesion and the time needed for day-to-day maintenance.
- Excellent flow and adhesion Easy and safe to apply.
- Tested according to DIN 51130, Anti-Slip Class R9 ( mat )
- Low odor. Emissions tested building product according to AgBB guidelines. abZ-No. Z-157.20-69 (Germany)

Available gloss grades (60°):

satin (10-20) / Crosslinker A Mixing ratio 5:1.

mat (5-10) / Crosslinker A Mixing ratio 5:1.

semi gloss (30-50) / Crosslinker A Mixing ratio 4:1.

Substrates:

- PVC / LVT with firm adhesion to the substrate. (\*\*\*)
- Linoleum
- Caoutchouc / rubber
- Epoxy leveling coatings / PU cast floorings
- Wood and cork floors after priming. Primer options: eukula classic prime 200 / G 200 A / eukula oil 1+FS, 2K with eukula master FS / eukula color oil FS, 2K with eukula master FS.
- After treatment of the substrate with Dr. Schutz PU Color.
- Non-absorbent stone and tile substrates after priming with Dr. Schutz Superbond.
- Cementitious decorative screeds if tested and approved by us. If necessary after priming with Dr. Schutz Primer for decorative screed floors. Tested for fire behavior in accordance with EN 13501 Class A2(fl)-s1. (\*)  
The suitability for safety floorings, more structured surfaces and studded floors must be clarified in advance on a project-specific basis. Please take note of our specific floor finishing instructions under [www.dr-schutz.com](http://www.dr-schutz.com).

The combination with Dr. Schutz Adds is possible and extends the range of application:

- Duro Plus L Add leads to an increased matting and a harder surface.
- R10 Antislip Add results in a significant anti-slip effect.
- R11 Antislip Add structures the surface leading to a high slip resistance.
- Decelerator Add extends the working time on the surface.

## PU Anticolor

- Flex Add for soft PU cast coatings and other more point-elastic substrates with Shore D < 60  
The product information of the above-mentioned products also applies.

### 2. APPLICATION

Shake up well. Mix Crosslinker carefully and evenly into the base lacquer, mix again after a maturing time of approx. 10 minutes. Do not mix more than is consumed within 2 hours. Apply evenly using the Dr. Schutz Aquatop roller at a temperature of at least 15 °C to the substrate prepared for the application (refer to our Technical Information "Basic cleaning of substrates").

Please note:

- The substrate must be properly prepared. It must be sound, free from residues of care products and loose coating layers and be in a abraded, clean, dry condition, free of oil, wax and dust. (\*\*)
- Clean tools with water. Hardened coating residues can only be removed mechanically. We always recommend the use of new dry paint rollers.
- The temperature of the floor and material must not fall below +15°C during application and drying time. Ideal conditions are in the range of 18-25 °C.
- The technical rules are to be observed.

### 3. CONSUMPTION

2 coats of 50 ml/m<sup>2</sup> per coat on non-absorbent but porous and more heavily abraded surfaces. (Example: open-pored linoleum, worn coverings in the renovation process).

1 coat of 100 ml/m<sup>2</sup> on non-absorbent, non-abraded substrate. (Example: resealing of new coverings with intact factory finish).

2 thick coats of approx. 100 ml/m<sup>2</sup> (10 m<sup>2</sup>/l) per coat on absorbent substrates (wood, concrete, screed floor) after proper priming.

### 4. DRYING TIME

Can be carefully walked on, or worked on again after the water has evaporated (1- 3 hours) . If left to dry for more than 48 hours before a second application, the surface must be fully abraded. Can be used with caution 12 hours after the last layer has dried. About 80% of the wear resistance is already reached after 24 hours. The product is completely resistant after 7 days.

Please note:

- Low temperatures, increased air humidity and poor ventilation can significantly extend the drying time.
- The evaporation of water can be accelerated by ventilation. We recommend our Dr. Schutz TG1 drying fan.
- The area should not be wet-mopped in the first 3 days afterwards.
- Refrain from placing rugs in the first 10-14 days. Carefully place the furniture.
- Covers for protection during further work should be applied after 3 days at the earliest. We recommend the breathable and slip-protected Dr. Schutz Protect Fleece.

## PU Anticolor

### 5. CLEANING & MAINTENANCE

Once the hardening is complete, use Dr. Schutz PU Cleaner for day-to-day cleaning. PU Cleaner

In areas where conventional maintenance is not carried out due to high resistance requirements and to maintain specific surface properties, signs of wear such as scratches or discoloration might make a partial or complete restoration of the coating layer through a renewed coating application necessary as a maintenance measure. We always recommend renovating in closed off partial areas.

In case conventional care is requested, we recommend Dr. Schutz Floor Mat or Dr. Schutz Floor Shine, depending on the gloss grade of the finish.

Preventive measures (e.g. entrance mats or zones) are required in areas of strong wear and tear (e.g. chair castors, sand, ...). These areas require intensive maintenance or an early restoration depending on the extent of the damage.

Please take note of our specific floor care guides under [www.dr-schutz.com](http://www.dr-schutz.com).

### 6. STORAGE

Protect from frost. Store in a cool dry place. Keep out of the reach of children.

Shelf life in unopened original containers from date of manufacture: 12 months. Note the imprinted date of manufacture.

If stored in changing temperatures and in opened canisters, dry particles can form. Filter these out with a sieve before using.

### 7. TECHNICAL DATA

Ingredients: water / polyacrylate / polyurethane / glycol ether / silicic acids / waxes / additives / preservation agents

Decopaint 2004/42/IIA(j)(140)140 / GISCODE W3/DD+ (2 component waterbased lacquer, VOC 5-15%, NMP-free)

ADR/RID: Not a dangerous good as defined by transport regulations.

CLP/GHS:

Base lacquer: no labelling obligation. UFI: XQ30-X0F3-Q009-8K4W satin / 30J0-D0EN-6000-TGFW mat / 0410-R0R6-H00F-EANY semi gloss

Crosslinker: GHS07, Warning. Contains isocyanates. May produce an allergic reaction. UFI: NS30-F04H-000S-XWQY Further information on labelling and on safe handling can be found in the current Safety Data Sheet.

Even when using low-pollution products, the usual safety measures are to be observed. Keep away from children. Completely emptied containers can be disposed of with household waste or with the collection of recyclables.

### 8. SPECIAL NOTES

- Mixed twopart products can develop carbon dioxide and pressure. Never close twopart mixtures tightly, danger of bursting!

## PU Anticolor

- Please pay attention to the printed batch number. Only use products with the same batch number in one layer. In the case of different batches, mix these in a separate container before using.
- All indications based on 23°C/50% rH/ 3-fold change of air per hour. Existing conditions can vary and account for different results.
- Please note: coloured products (hair-dyes, wound disinfectants, etc.) must be removed from the sealer film as soon as possible. The longer such aggressive colouring chemicals are allowed to soak in, the more likely they will migrate and leave stains. Depending on the type of stain and exposure time they can sometimes not be fully removed. Therefore treat stains immediately with Dr. Schutz Elatex and follow these instructions: dab off any fluid colour with absorbent cloths. Spray the stain with Dr. Schutz Elatex and let it soak in for 5 minutes. Dab the stain from its edge to its centre with a soft cloth. Do not rub. Finally, treat with clear water.
- If a specific resistance is required for specific areas (e.g. to disinfectants, dyeing products or chemicals), we recommend appropriate preliminary tests with the products used on site.
- In case of permanent or recurring exposure to aggressive influences (e.g. hand sanitiser dispensers, tyres, chair castors, etc.) we recommend protective underlays.
- In case of an underfloor heating system, follow the instructions of the flooring manufacturer.
- The suitability of floating floor coverings must be determined in view of the process and the water used.
- Light decomposable substrates (EP, rubber) can degrade under a clear coat in areas that are strongly exposed to light, which can occasionally lead to loss of lacquer adhesion. In this case we recommend lightproof coating with PU Color.
- (\*\*\*) Application on chlorine-free vinyl floor coverings, so-called polyolefin floor coverings, cannot be guaranteed.

### 9. CROSS-REFERENCE

Our following publications in their updated form are valid as an integral part of this fact sheet:

- General notes on the application of Dr. Schutz surface products.
  - Safety Data Sheet available on request.
  - (\*) Please pay attention to Technical Information 300 “Sealing decorative screed floors”.
  - (\*\*) Please pay attention to our Technical Information 002 „Preparation of subsurfaces”.
- [www.dr-schutz.com](http://www.dr-schutz.com) / The quoted printed matter, as well as this Product Information in its updated form, is available on our homepage or on request from the address quoted below.

## PU Anticolor

### Dr. Schutz - We Care About Floors

Headquarter (international)  
Germany

Dr. Schutz GmbH  
Holbeinstraße 17  
53175 Bonn  
Germany

phone +49 (228) 95352-40  
fax +49 (228) 95352-46  
email: [export@dr-schutz.com](mailto:export@dr-schutz.com)  
[www.dr-schutz.com](http://www.dr-schutz.com)

United Kingdom

Dr. Schutz UK Ltd.  
Unit 24, Anglo Business Park,  
Smeaton Close, Aylesbury Bucks  
HP19 8UP  
United Kingdom

contact: Richard Nelson  
phone +44 (1296) 437827  
fax +44 (1296) 334219  
email: [richard@drschutz.co.uk](mailto:richard@drschutz.co.uk)

Ireland

Dr. Schutz Ireland  
35 Pic Du Jer Park,  
Ballinlough, Cork  
T12 R9F9  
Republic of Ireland

contact: Paul O'Reardon  
mobile +353 87 767 8388  
email: [paul@drschutzireland.com](mailto:paul@drschutzireland.com)

The above advice for technical application is given to the best of our knowledge and according to the latest state of technology. Therefore, if our products are used carefully heeding the advice given on their application, as well as following our suggested procedures with the materials intended for use with these products, no damage shall occur. However, our products are used outside and beyond our possible control, and are therefore subject to your own responsibility, which does not release you from the obligation to check for yourself whether our supplied products are suitable for your intended purpose and procedure. Therefore our notes and advice are not legally binding and cannot be used against us as grounds for liability - which includes the rights and protection of any third party. The relevant recommendations, guidelines and standard norms are to be observed, as well as the recognized technical rules. On publication, this product information replaces and supersedes the validity of any previous versions.