



EpiMax SAFETY DATA SHEET

Product Name **EpiMax 237 PART A**

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name	EPIMAX TECHNOLOGIES PTY LTD
Address	23 Hargraves Place, Wetherill Park NSW 2164
Telephone	1300 721 522
Email	info@epimax.com.au
Emergency	13 11 26
Synonym(s)	237 PART A • 40237400 – PRODUCT CODE • EPOXIDE RESIN
Use(s)	TWO PART EPOXY RESIN COMPOSITION. USE WITH EPIMAX 237 PART B
SDS Date	17/07/23

2. HAZARDS IDENTIFICATION

GHS Classification	Flammable Liquids Category : 3 Skin Corrosion / Irritation – Category 2 Serious Eye Damage / Eye Irritation Category: 1 Skin Sensitization Category :1 Specific Target Organ Toxicity (Repeated Exposure) Category: 2
--------------------	---

Signal Word DANGER



HAZARD STATEMENTS

H226	Flammable liquid and vapour
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation

PREVENTION STATEMENTS

P102	Keep out of reach of children
P103	Read label before use
P210	Keep away from all sources of ignition – no smoking
P233	Keep in container tightly closed
P240	Ground/ Bond container and receiving equipment

Product Name: EpiMax 237 PART A

- P241 Use explosion- proof electrical, ventilating, lighting and all other equipment
- P242 Use only non-sparking tools
- P261 Avoid breathing mist, vapours or spray
- P264 Wash hands, face and all exposed skin thoroughly after handling
- P272 Contaminated work clothing should not be allowed out of the work place
- P273 Avoid release to the environment
- P280 Wear protective clothing, gloves, eye face / protection and suitable respirator

RESPONSE STATEMENTS

- P101 If medical advice is needed, have product container or label at hand
- P302+352 IF ON SKIN: Wash with soap and water
- P303+361+353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing
- P363 Wash contaminated clothing before reuse
- P333+313 If skin irritation or a rash occurs: Get medical advice / attention
- P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses
- P337+313 If eye irritation persists get medical advice / attention
- P370+378 In case of fire: Use alcohol resistant foam for extinction
- P391 Collect spillage

STORAGE STATEMENTS

- P404+235 Store in a well ventilated place. Keep cool.

DISPOSAL STATEMENTS

- P501 Dispose of contents/container in accordance with local, regional, national and international regulations

UN No.	1866	DG CLASS	3	Subsidiary Risk(s)	None Allocated
Packing Group	NONE ALLOCATED	Hazchem Code	3[Y]		

3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS NO.	Content
XYLENE	NOT AVAILABLE	001330-20-7	30% - <60%
BISPHENOL A EPOXY RESIN	NOT AVAILABLE	025068-38-6	30% - <60%
M.I.B KETONE	NOT AVAILABLE	000108-10-1	10% - <30%
PARMETOL DF 18	NOT AVAILABLE	098726-06-8	<10%
NON-HAZARDOUS INGREDIENTS OR THOSE BELOW CUT OFF LIMITS			

4. FIRST AID MEASURES

Eye Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Inhalation Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Product Name: EpiMax 237 PART A

Skin	Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Special Treatment	Treat symptomatically.

5. FIRE FIGHTING MEASURES

Special Hazards	Flammable. May evolve toxic gases (carbon oxides, phenols, hydrocarbons) when heated to decomposition. Eliminate all ignition sources including cigarettes, open flames, spark producing switches/tools, heaters, naked lights, pilot lights, mobile phones etc. when handling. Earth containers when dispensing fluids.
Advice for firefighters	Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.
Extinguishing Media	Dry agent, carbon dioxide or water fog. Prevent contamination of drains or waterways. DO NOT USE WATER JET
Hazchem Code	3[Y]

6. ACCIDENTAL RELEASE MEASURES

Spillage	Contact emergency services where appropriate. Use personal protective equipment. Clear area of all unprotected personnel. Ventilate area where possible. Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. Eliminate all ignition sources.
-----------------	--

7. STORAGE AND HANDLING

Storage	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Use only with adequate ventilation. Wear
----------------	--

Product Name:

EpiMax 237 PART A

appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

8. EXPOSURE CONTROLS / PERSONAL PROTECTIONS

Exposure Stds

Ingredient	Reference	TWA		STEL	
Xylene	SWA (Aus)	80ppm	350mg/m ³	150ppm	655mg/ m ³
Butan-1-ol	SWA (AUS)	50ppm	152mg/ m ³		
Ethylbenzene	SWA (AUS)	100ppm	434mg m ³	125ppm	543mg/ m ³

Biological Limits No biological limit allocated.

Engineering Controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof extraction ventilation is recommended. Flammable/explosive vapours may accumulate in poorly ventilated areas. Vapours are heavier than air and may travel some distance to an ignition source and flash back. Maintain vapour levels below the recommended exposure standard.

PPE Wear splash-proof goggles, nitrile or viton (R) gloves, coveralls and a Type A (Organic vapour) respirator. If sanding dry product, wear: a Class P1 (Particulate) respirator. If spraying, with prolonged use, or if in confined areas, wear: impervious coveralls and an Air-line respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	AMBER LIQUID	Solubility (water)	Insouble
Odour	NOT AVAILABLE	Specific Gravity	0.97
pH	NOT AVAILABLE	% Volatiles	50%
Vapour Pressure	NOT AVAILABLE	Flammability	FLAMMABLE
Vapour Density	NOT AVAILABLE	Flash Point	24°C (Closed Cup)
Boiling Point	NOT DETERMINED	Upper Explosion Limit	11.3%
Melting Point	NOT AVAILABLE	Lower Explosion Limit	0.8%
Evaporation Rate	NOT AVAILABLE		
Autoignition Rate	NOT DETERMINED	Decomposition Temperature	NOT AVAILABLE
Partition Coefficient	NOT AVAILABLE	Viscosity	NOT AVAILABLE

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under recommended conditions of storage.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources.
Material to avoid	Incompatible with oxidising agents (eg. hypochlorites), acids (eg. nitric acid), alkalis (eg. hydroxides), heat and ignition sources.
Hazardous Decomposition Products	May evolve toxic gases (carbon oxides, phenols, hydrocarbons) when heated to decomposition.
Hazardous Reactions	Hazardous polymerization is not expected to occur.

11. TOXICOLOGICAL INFORMATION

Health hazard summary	This product has the potential to cause adverse health effects with over exposure. Use safe work practices to avoid eye or skin contact and inhalation. May cause sensitisation by skin contact. The cured product is considered non toxic.
Eye	Contact may result in irritation, lacrimation, pain, redness and conjunctivitis. May result in burns with prolonged contact.
Inhalation	Over exposure may result in irritation of the nose and throat, with coughing. High level exposure may result in dizziness, drowsiness, breathing difficulties, pulmonary oedema and unconsciousness. May cause sensitisation by inhalation.
Skin	Contact may result in irritation, redness, rash and dermatitis. May cause sensitisation by skin contact.
Ingestion	Moderate toxicity. Ingestion may result in nausea, vomiting, abdominal pain, diarrhoea, fatigue, dizziness and unconsciousness.
Toxicity Data	There is no toxicological information available for this product.

12. ECOLOGICAL INFORMATION

Other adverse effects	Limited ecotoxicity data was available for this product at the time this report was prepared. Ensure appropriate measures are taken to prevent this product from entering the environment.
------------------------------	--

13. DISPOSAL CONSIDERATIONS

Waste disposal	Mix parts A + B together (small amounts), absorb with sand, vermiculite or similar and dispose of to an approved landfill site. Ensure protective equipment is worn when mixing. Do not seal containers/tins until reaction is complete. Contact the manufacturer for additional information. Prevent contamination of drains or waterways as environmental damage may result.
Legislation	Dispose of in accordance with relevant local legislation.

Product Name: **EpiMax 237 PART A**

14. TRANSPORT INFORMATION



CLASSIFIED AS A DANGEROUS GOOD THE CRITERIA OF THE ADG CODE

Shipping Name	FLAMMABLE LIQUID N.O.S				
UN No.	1866	DG CLASS	3	Subsidiary Risk(s)	NONE ALLOCATED
Packing Group	NONE ALLOCATED	Hazchem Code	3[Y]		

IATA

Shipping Name	FLAMMABLE LIQUID N.O.S				
UN No.	1866	DG CLASS	3	Subsidiary Risk(s)	NONE ALLOCATED
Packing Group	NONE ALLOCATED	Hazchem Code	3[Y]		

IMDG

Shipping Name	FLAMMABLE LIQUID N.O.S				
UN No.	1866	DG CLASS	3	Subsidiary Risk(s)	NONE ALLOCATED
Packing Group	NONE ALLOCATED	Hazchem Code	3[Y]		

15. REGULATORY INFORMATION

Poison Schedule Classified as a Schedule 5 (S5) Poison using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).

AICS All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Additional information This product is used in conjunction with EpiMax 237 PART B.

WELDING - SANDING - CUTTING DRIED OR CURED PRODUCT: If sanding, cutting or welding dried or cured product, adverse health effects may be avoided by the use of appropriate engineering controls and/or personal protective equipment. If welding, wear a Class P2 (Metal fume) respirator and depending on the nature of the surface being welded, additional protection (eg. for organic vapours/acid gas) may also be required. A Class P1 (Particulate) respirator is recommended if dust is generated.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

ABBREVIATIONS:

ACGIH - American Conference of Industrial Hygienists.

ADG - Australian Dangerous Goods.

BEI - Biological Exposure Indices.

Product Name:

EpiMax 237 PART A

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

CNS - Central Nervous System.

EC No - European Community Number.

HSNO - Hazardous Substances and New Organisms.

IARC - International Agency for Research on Cancer.

mg/m³ - Milligrams per Cubic Metre.

NOS - Not Otherwise Specified.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

PPM - Parts Per Million.

RTECS - Registry of Toxic Effects of Chemical Substances.

STEL - Short Term Exposure Limit.

SWA - Safe Work Australia.

TWA - Time Weighted Average.



EpiMax SAFETY DATA SHEET

Product Name **EpiMax 237 PART B**

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name	EPIMAX TECHNOLOGIES PTY LTD
Address	23 Hargraves Place, Wetherill Park NSW 2164
Telephone	1300 721 522
Fax	(02) 9904 3207
Emergency	1300 721 522
Synonym(s)	237 PART B • 5023740 – PRODUCT CODE • EPOXIDE RESIN
Use(s)	TWO PART EPOXY RESIN COMPOSITION. USES WITH EPIMAX 237 PART A
SDS Date	17/07/23

2. HAZARDS IDENTIFICATION



HAZARD STATEMENTS

H226	Flammable liquid and vapour
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H317	May cause an allergic reaction
H318	Causes serious eye damage
H332	Harmful if inhaled

PREVENTION STATEMENTS

P102	Keep out of reach of children
P103	Read label before use
P210	Keep away from all sources of ignition – no smoking
P233	Keep container tightly closed
P240	Ground / bond container and receiving equipment

Product Name: EpiMax 237 PART B

P241	Use explosion-proof electrical, ventilating, lighting and all other equipment
P242	Use only-non-sparking tools
P243	Take precautionary measures against static discharge
P260	Do not breathe mist, vapours or spray
P264	Wash hands, face and all exposed skin thoroughly after handling
P270	Do not eat, drink or smoke when using this product
P271	Use only outdoors or in a well-ventilated area
P272	Contaminated work clothing should not be allowed out of the work place
P280	Wear protective clothing, gloves, eye/face protection and suitable respirator as required

RESPONSE STATEMENTS

P101	If medical advice is needed, have product container or label at hand
P301+310	IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician
P301+330+331	IF SWALLOWED: Rinse mouth.
P302+352	IF ON SKIN: Wash with soap and water
P303+361+353	IF ON SKIN 9or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/shower
P363	Wash contaminated clothing before reuse
P333+313	If skin irritation or a rash occurs: Get medical advice/attention
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P310	Immediately call a POISON CENTRE or doctor/physician
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and continue rinsing.
P310	Immediately call a POISON CENTRE or doctor/physician
P370+378	In case of fire, use water fog, foam or dry agents for extinction.

STORAGE STATEMENTS

P405	Store locked up
P403+235	Store in a well ventilated place. Keep cool.

DISPOSAL STATEMENTS

P501	Dispose of contents/container in accordance with local, regional, national and international regulations
------	--

UN No.	1866	DG CLASS	3.2	Subsidiary Risk(s)	None Allocated
Packing Group	II	Hazchem Code	3[Y]		

3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS NO.	Content
XYLENE	NOT AVAILABLE	001330-20-7	30% - <60%
POLYAMIDE RESIN	NOT AVAILABLE	PROPRIETARY	10% - <30%
PM SOLVENT	NOT AVAILABLE	000107-98-2	10% - <30%
PARMETOL DF 18	NOT AVAILABLE	098726-06-8	<10%
NON-HAZARDOUS INGREDIENTS OF THOSE BELOW CUT OFF LIMITS			

Product Name: **EpiMax 237 PART B**

4. FIRST AID MEASURES

Eye Immediately irrigate with copious quantities of water for 15 minutes. Eyelids to be held open. Remove clothing if contaminated and wash skin. Urgently seek medical assistance. Transport to hospital or medical centre.

Inhalation Remove victim from exposure- avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If breathing laboured and patient cyanotic (blue), ensure airways are clear and have a qualified person give oxygen through a facemask. If breathing has stopped apply artificial respiration at once. In the even of cardiac arrest, apply external cardiac massage. Seek immediate medical advice.

Skin For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble). For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance. Components of the material can be absorbed through the skin with resultant toxic effects.

Ingestion Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Get to a doctor or hospital quickly.

Special Treatment Treat symptomatically.

5. FIRE FIGHTING MEASURES

Special Hazards Flammable. May evolve toxic gases (carbon oxides, phenols, hydrocarbons) when heated to decomposition. Eliminate all ignition sources including cigarettes, open flames, spark producing switches/tools, heaters, naked lights, pilot lights, mobile phones etc. when handling. Earth containers when dispensing fluids.

Advice for firefighters Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

Extinguishing Media Dry agent, carbon dioxide or water fog. Prevent contamination of drains or waterways

Hazchem Code •2W

6. ACCIDENTAL RELEASE MEASURES

Spillage Contact emergency services where appropriate. Use personal protective equipment. Clear area of all unprotected personnel. Ventilate area where possible. Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. Eliminate all ignition sources.

7. STORAGE AND HANDLING

Storage Store tightly sealed in a cool, dry, well ventilated area, removed from oxidising agents, acids, alkalis, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled,

Product Name: EpiMax 237 PART B

protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should be banded and have appropriate fire protection and ventilation systems.

Precautions for safe handling Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

8. EXPOSURE CONTROLS / PERSONAL PROTECTIONS

Exposure Stds No exposure standard(s) allocated.

Biological Limits No biological limit allocated.

Engineering Controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended.

PPE Wear splash-proof goggles, nitrile or viton (R) gloves, coveralls and a Type A (Organic vapour) respirator. If sanding dry product, wear: a Class P1 (Particulate) respirator. If spraying, with prolonged use, or if in confined areas, wear: impervious coveralls and an Air-line respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	AMBER LIQUID	Solubility (water)	Insoluble
Odour	SLIGHTLY AMMONIACAL	Specific Gravity	0.97
pH	NOT AVAILABLE	% Volatiles	55%
Vapour Pressure	NOT AVAILABLE	Flammability	FLAMMABLE
Vapour Density	NOT AVAILABLE	Flash Point	41°C
Boiling Point	NOT DETERMINED	Upper Explosion Limit	NOT AVAILABLE
Melting Point	NOT AVAILABLE	Lower Explosion Limit	NOT AVAILABLE
Evaporation Rate	NOT AVAILABLE		
Autoignition Rate	NOT DETERMINED	Decomposition Temperature	NOT AVAILABLE
Partition Coefficient	NOT AVAILABLE	Viscosity	NOT AVAILABLE

10. STABILITY AND REACTIVITY

Chemical Stability Stable under recommended conditions of storage.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources.

Material to avoid Incompatible with oxidising agents (eg. hypochlorites), acids (eg. nitric acid), alkalis (eg. hydroxides), heat and ignition sources.

Hazardous Decomposition Products May evolve toxic gases (carbon oxides, phenols, hydrocarbons) when heated to decomposition.

Hazardous Reactions Hazardous polymerization is not expected to occur.

11. TOXICOLOGICAL INFORMATION

Product Name: EpiMax 237 PART B

Health hazard summary This product has the potential to cause adverse health effects with over exposure. Use safe work practices to avoid eye or skin contact and inhalation. May cause sensitisation by skin contact. The cured product is considered non toxic.

Eye Irritant. Contact may result in irritation, lacrimation, pain, redness and conjunctivitis. May result in burns with prolonged contact.

Inhalation Over exposure may result in irritation of the nose and throat, with coughing. Due to low vapour pressures, it is not thought to be an inhalation hazard.

Skin Irritant . Contact may result in irritation, redness, rash and dermatitis. Can cause burns. May cause sensitisation by skin contact.

Ingestion Irritant. Moderate toxicity. Ingestion may result in nausea, vomiting, abdominal pain, diarrhoea, fatigue, dizziness and unconsciousness.

Toxicity Data There is no toxicological information available for this product.

12. ECOLOGICAL INFORMATION

Other adverse effects Limited ecotoxicity data was available for this product at the time this report was prepared. Ensure appropriate measures are taken to prevent this product from entering the environment.

13. DISPOSAL CONSIDERATIONS

Waste disposal Mix parts A + B together (small amounts), absorb with sand, vermiculite or similar and dispose of to an approved landfill site. Ensure protective equipment is worn when mixing. Do not seal containers/tins until reaction is complete. Contact the manufacturer for additional information. Prevent contamination of drains or waterways as environmental damage may result.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION



CLASSIFIED AS A DANGEROUS GOOD THE CRITERIA OF THE ADG CODE

Shipping Name	FLAMMABLE LIQUID, N.O.S				
UN No.	1866	DG CLASS	3.2	Subsidiary Risk(s)	NONE ALLOCATED
Packing Group	NONE ALLOCATED	Hazchem Code	3[Y]		

IATA

Shipping Name	FLAMMABLE LIQUID, N.O.S				
UN No.	1866	DG CLASS	3.2	Subsidiary Risk(s)	NONE ALLOCATED
Packing Group	NONE ALLOCATED	Hazchem Code	3[Y]		

Product Name: **EpiMax 237 PART B**

IMDG

Shipping Name	FLAMMABLE LIQUID, N.O.S				
UN No.	1866	DG CLASS	3.2	Subsidiary Risk(s)	NONE ALLOCATED
Packing Group	NONE ALLOCATED	Hazchem Code	3[Y]		

15. REGULATORY INFORMATION

Poison Schedule Classified as a Schedule 5 (S5) Poison using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).

AICS All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Additional information This product is used in conjunction with EpiMax 237 PART A.

WELDING - SANDING - CUTTING DRIED OR CURED PRODUCT: If sanding, cutting or welding dried or cured product, adverse health effects may be avoided by the use of appropriate engineering controls and/or personal protective equipment. If welding, wear a Class P2 (Metal fume) respirator and depending on the nature of the surface being welded, additional protection (eg. for organic vapours/acid gas) may also be required. A Class P1 (Particulate) respirator is recommended if dust is generated.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

ABBREVIATIONS:

ACGIH - American Conference of Industrial Hygienists.

ADG - Australian Dangerous Goods.

BEI - Biological Exposure Indices.

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

CNS - Central Nervous System.

EC No - European Community Number.

HSNO - Hazardous Substances and New Organisms.

IARC - International Agency for Research on Cancer.

mg/m³ - Milligrams per Cubic Metre.

NOS - Not Otherwise Specified.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

PPM - Parts Per Million.

RTECS - Registry of Toxic Effects of Chemical Substances.

STEL - Short Term Exposure Limit.

SWA - Safe Work Australia.

TWA - Time Weighted Average.